ATB-AGM-GP12-150

Sealed AGM power.
Built for standby duty.

A 12 V 155 Ah general-purpose AGM VRLA battery for UPS, telecom, security and emergency lighting systems and energy storage. Valve-regulated oxygen-recombination construction with corrosion-resistant alloy grids, a high-strength AGM separator and high-purity active materials gives low self-discharge and long service life, in a sealed, maintenance-free, non-spillable package with M8 bolt terminals.



12 V	155 Ah	1200 A	44.5 kg
NOMINAL VOLTAGE	C20 CAPACITY @ 25°C	MAX DISCHARGE (5 S)	APPROX. WEIGHT

Sealed AGM VRLA
Valve-regulated oxygen-recombination design. Maintenance-free and non-spillable: no electrolyte topping and no acid handling.

M8 bolt terminals
Threaded M8 terminals for secure bolted cable connections in UPS, telecom and storage systems.

Long service life
Corrosion-resistant alloy grids and a high-strength AGM separator with high-purity active materials give low self-discharge and long float life.

Standard footprint
482 × 170 × 240 mm case for battery cabinets, racks and UPS enclosures.

SPECIFICATIONS


MECHANICAL

Length	**482 mm ±2.5**
Width	**170 mm ±1.5**
Container height	**240 mm ±2.5**
Overall height	**240 mm ±2.5**
Approx. weight	**44.5 kg ±3%**
Container material	**ABS, UL94-HB (UL94-V0 optional)**
Terminal type	**M8 bolt terminal**

ELECTRICAL

Nominal voltage	**12 V**
Chemistry	**AGM VRLA (sealed)**
Capacity, 20 hr (C20)	**155 Ah**
Capacity, 10 hr (C10)	**150 Ah**
Capacity, 5 hr (C5)	**131.5 Ah**
Rating basis	**to 1.80 V/cell @ 25°C**
Float voltage @ 25°C	**13.5 – 13.8 V**
Equalizing voltage @ 25°C	**14.4 – 15.0 V**
Max charge current	**45 A**
Max discharge current	**1200 A (5 s)**
Internal resistance (charged)	**≈ 4.0 mΩ**
Operating temp. (dis / chg)	**−15°C~50°C / −15°C~40°C**
Storage temp.	**−15°C~40°C**

CONTAINER DRAWING — DIMENSIONS IN MM



ATB-AGM-GP12-150 — technical data

CONSTANT CURRENT DISCHARGE @ 25°C · UNIT: A

F.V (V/cell) / Time	30 min	45 min	1 h	3 h	5 h	8 h	10 h	20 h
1.60 V	155	112	93.8	40.9	28.2	18.8	15.6	8.07
1.67 V	152	110	92.4	40.6	27.8	18.5	15.5	7.97
1.70 V	150	109	91.1	40.2	27.2	18.2	15.3	7.88
1.75 V	147	107	89.3	39.4	26.7	17.9	15.2	7.80
1.80 V	144	103	85.1	38.7	26.3	17.9	15.0	7.73
1.85 V	133	96.9	82.1	35.7	25.1	17.0	14.0	7.44

CONSTANT POWER DISCHARGE @ 25°C · UNIT: W/CELL

F.V (V/cell) / Time	30 min	45 min	1 h	3 h	5 h	8 h	10 h	20 h
1.60 V	284	208	176	78.3	54.5	36.8	30.3	15.9
1.67 V	282	207	175	78.0	53.9	36.3	30.0	15.8
1.70 V	280	205	173	77.6	53.0	35.9	29.7	15.6
1.75 V	277	202	171	76.4	52.4	35.4	29.4	15.5
1.80 V	274	196	164	75.2	51.6	35.3	29.3	15.3
1.85 V	253	186	159	69.6	49.2	33.6	27.9	14.8

EFFECT OF TEMPERATURE ON CAPACITY (10 HR)

Temperature	Capacity (10 HR)
40 °C	102%
25 °C	100%
0 °C	85%
−15 °C	65%


SELF-DISCHARGE CHARACTERISTICS

Storage time	Remaining capacity
3 months	91%
6 months	82%
12 months	64%

CHARACTERISTIC CURVES


Discharge Characteristics

TERMINAL VOLTAGE (V/CELL) vs DISCHARGE TIME · 25°C / 20°C




Charging Characteristics

0.1 CA · 2.25 V/CELL @ 25°C




Capacity Retention (Self-Discharge)

CAPACITY RETENTION RATIO vs STORAGE TIME



Float Service Life

FLOAT LIFE vs BATTERY TEMPERATURE · 2.25 V/CELL



STANDARDS & QUALITY

AGM VRLA batteries produced by an ATB-approved manufacturing partner whose VRLA batteries are UL-recognized components under UL 1989, in facilities certified to ISO 9001, ISO 14001 and ISO 45001. Sealed, non-spillable VRLA construction.

Values are subject to variation of ±5% under normal manufacturing processes. Technical specifications are subject to change without prior notice. Curves represent typical performance for the AGM VRLA cell platform at the stated reference conditions. This product is engineered, specified and branded by ATB Power. E&OE. © ATB Power.