ATB-AGM-HR12-120

High-rate AGM.
Power for UPS bursts.

A 12 V 30 Ah high-rate AGM VRLA battery for short-duration, high-current UPS discharge. Sealed, maintenance-free and non-spillable, with M5 bolt terminals.



12 V	120 W	450 A	9.0 kg
NOMINAL VOLTAGE	PER CELL · 15 MIN TO 1.67 V	MAX DISCHARGE (5 S)	APPROX. WEIGHT

Sealed AGM VRLA
Valve-regulated oxygen-recombination design. Maintenance-free and non-spillable: no electrolyte topping and no acid handling.

M5 bolt terminals
Threaded M5 terminals for secure bolted cable connections in UPS and standby systems.

High-rate discharge
Optimised for short, high-current discharge in UPS systems.

Standard footprint
165 × 126 × 175 mm case.

SPECIFICATIONS


MECHANICAL

Length	**165 mm ±1.5**
Width	**126 mm ±1.5**
Container height	**175 mm ±2.0**
Overall height	**175 mm ±2.0**
Approx. weight	**9.0 kg ±5%**
Container material	**ABS, UL94-HB (UL94-V0 optional)**
Terminal type	**M5 bolt terminal**

ELECTRICAL

Nominal voltage	**12 V**
Chemistry	**AGM VRLA (sealed)**
Nominal capacity	**120 W/cell (15 min to 1.67 V/cell, 25°C) · 30 Ah (C20) · 18.8 Ah (C1)**
Float voltage @ 25°C	**13.5 – 13.8 V**
Equalizing voltage @ 25°C	**14.4 – 15.0 V**
Max charge current	**9.00 A**
Max discharge current	**450.00 A (5 s)**
Internal resistance (charged)	**≈ 11.5 mΩ**
Operating temp. (dis / chg)	**−15°C~50°C / −15°C~40°C**
Storage temp.	**−15°C~40°C**

CONTAINER DRAWING — DIMENSIONS IN MM



ATB-AGM-HR12-120 — technical data

CONSTANT CURRENT DISCHARGE @ 25°C · UNIT: A

F.V (V/cell) / Time	5 min	8 min	10 min	15 min	20 min	30 min	60 min	1.5H
1.60 V	123	94.4	85.3	64.1	50.9	35.0	19.9	15.1
1.67 V	119	91.7	81.6	62.1	49.5	34.6	19.9	14.7
1.70 V	117	89.0	79.1	60.0	48.1	34.3	19.2	14.4
1.75 V	112	84.7	75.9	57.9	46.0	33.2	18.8	14.1
1.80 V	108	80.7	71.8	55.5	44.1	31.8	18.3	13.9

CONSTANT POWER DISCHARGE @ 25°C · UNIT: W/CELL

F.V (V/cell) / Time	5 min	8 min	10 min	15 min	20 min	30 min	60 min	1.5H
1.60 V	226	176	161	124	100	68.6	39.5	30.1
1.67 V	220	172	155	120	97.1	68.0	39.4	29.3
1.70 V	217	168	151	117	94.5	67.3	38.2	28.6
1.75 V	210	161	146	113	90.3	65.3	37.4	28.1
1.80 V	203	155	139	109	86.6	62.6	36.5	27.7

EFFECT OF TEMPERATURE ON CAPACITY (20 HR)

Temperature	Capacity (20 HR)
40 °C	102%
25 °C	100%
0 °C	85%
−15 °C	65%


SELF-DISCHARGE CHARACTERISTICS

Storage time	Remaining capacity
3 months	91%
6 months	82%
12 months	64%

CHARACTERISTIC CURVES


Discharge Characteristics

TERMINAL VOLTAGE (V/CELL) vs DISCHARGE TIME · 25°C / 20°C




Charging Characteristics

0.1 CA · 2.25 V/CELL @ 25°C




Capacity Retention (Self-Discharge)

CAPACITY RETENTION RATIO vs STORAGE TIME



Float Service Life

FLOAT LIFE vs BATTERY TEMPERATURE · 2.25 V/CELL



STANDARDS & QUALITY

AGM VRLA batteries produced by an ATB-approved manufacturing partner whose VRLA batteries are UL-recognized components under UL 1989, in facilities certified to ISO 9001, ISO 14001 and ISO 45001. Sealed, non-spillable VRLA construction.

Values are subject to variation of ±5% under normal manufacturing processes. Technical specifications are subject to change without prior notice. Curves represent typical performance for the AGM VRLA cell platform at the stated reference conditions. This product is engineered, specified and branded by ATB Power. E&OE. © ATB Power.